

Glycol Recovery Vehicles

GRV-800 & GRV-2000

Simple and Self Contained Solution

Easy One-Person Operation

Cost Effective

Rapid Fluid Recovery



Ready. Reliable. Responsive.

Glycol Recovery Vehicles

GRV-800 & GRV-2000

GRV-800	GRV-2000
800 USG (3,028 L) Tank	2,000 USG (7,571 L) Tank
Cylindrical, Mild Steel	Cylindrical, Mild Steel
Full Width and Hydraulically Raised	Full Width and Hydraulically Raised
50° with Hydraulic Cylinders	40° with Hydraulic Cylinders
Rear Dump 6" Gate	Rear Dump 6" Gate
5 in (12.7 cm); Quantity 2	5 in (12.7 cm); Quantity 2
Yes	Yes
Isuzu	Freightliner
14,500 lbs (6,577 kg)	33,000 lbs (14.968 kg)
Isuzu 4HK1-TC 4-Cylinder	Cummins B6.7
Aisin A465 6-Speed Automatic	Allison 2500 RDS Speed Automatic
132.5 in (336 cm)	224 in (568 cm)
132.3 111 (330 611)	,
30 USG (114 L)	50 USG (189 L)
, ,	50 USG (189 L)
, ,	50 USG (189 L) Positive Displacement 1700 CFM
30 USG (114 L) Positive Displacement 1420	Positive Displacement 1700
30 USG (114 L) Positive Displacement 1420 CFM	Positive Displacement 1700 CFM
30 USG (114 L) Positive Displacement 1420 CFM Cylindrical, Mild Steel	Positive Displacement 1700 CFM Cylindrical, Mild Steel
30 USG (114 L) Positive Displacement 1420 CFM Cylindrical, Mild Steel 25 USG (95 L)	Positive Displacement 1700 CFM Cylindrical, Mild Steel 45 USG (170 L)
30 USG (114 L) Positive Displacement 1420 CFM Cylindrical, Mild Steel 25 USG (95 L)	Positive Displacement 1700 CFM Cylindrical, Mild Steel 45 USG (170 L)
30 USG (114 L) Positive Displacement 1420 CFM Cylindrical, Mild Steel 25 USG (95 L) 83 in (211 cm)	Positive Displacement 1700 CFM Cylindrical, Mild Steel 45 USG (170 L) 94 in (239 cm)
30 USG (114 L) Positive Displacement 1420 CFM Cylindrical, Mild Steel 25 USG (95 L) 83 in (211 cm) CAT Tier IV Final Diesel	Positive Displacement 1700 CFM Cylindrical, Mild Steel 45 USG (170 L) 94 in (239 cm) Kubota Tier IV Final Diesel
30 USG (114 L) Positive Displacement 1420 CFM Cylindrical, Mild Steel 25 USG (95 L) 83 in (211 cm) CAT Tier IV Final Diesel 48 @ 2800 RPM (48 kW) 122 ft-lb @ 1600 RPM	Positive Displacement 1700 CFM Cylindrical, Mild Steel 45 USG (170 L) 94 in (239 cm) Kubota Tier IV Final Diesel 64 @ 2700 RPM (48.6 kW) 146 ft-lb @ 1600 RPM
30 USG (114 L) Positive Displacement 1420 CFM Cylindrical, Mild Steel 25 USG (95 L) 83 in (211 cm) CAT Tier IV Final Diesel 48 @ 2800 RPM (48 kW) 122 ft-lb @ 1600 RPM	Positive Displacement 1700 CFM Cylindrical, Mild Steel 45 USG (170 L) 94 in (239 cm) Kubota Tier IV Final Diesel 64 @ 2700 RPM (48.6 kW) 146 ft-lb @ 1600 RPM
30 USG (114 L) Positive Displacement 1420 CFM Cylindrical, Mild Steel 25 USG (95 L) 83 in (211 cm) CAT Tier IV Final Diesel 48 @ 2800 RPM (48 kW) 122 ft-lb @ 1600 RPM (165 Nm)	Positive Displacement 1700 CFM Cylindrical, Mild Steel 45 USG (170 L) 94 in (239 cm) Kubota Tier IV Final Diesel 64 @ 2700 RPM (48.6 kW) 146 ft-lb @ 1600 RPM (198.5 Nm)
Positive Displacement 1420 CFM Cylindrical, Mild Steel 25 USG (95 L) 83 in (211 cm) CAT Tier IV Final Diesel 48 @ 2800 RPM (48 kW) 122 ft-lb @ 1600 RPM (165 Nm) Included	Positive Displacement 1700 CFM Cylindrical, Mild Steel 45 USG (170 L) 94 in (239 cm) Kubota Tier IV Final Diesel 64 @ 2700 RPM (48.6 kW) 146 ft-lb @ 1600 RPM (198.5 Nm)
	Cylindrical, Mild Steel Full Width and Hydraulically Raised 50° with Hydraulic Cylinders Rear Dump 6" Gate 5 in (12.7 cm); Quantity 2 Yes Isuzu 14,500 lbs (6,577 kg) Isuzu 4HK1-TC 4-Cylinder Aisin A465 6-Speed



STANDARD FEATURES

- Paint: PPG Delfleet FDGU
- Paint Color Tank: Global White
- Emergency Shutdown Control System
- Back-up Alarm
- Overfill Sensor
- Pressure Washer
 - 3000 psi
 - 2.5 GPM
 - 100 USG (378L) Water Tank
- 3" Vacuum Tube
 - Sweeper Head Attachment
- 6" Diameter Vacuum Hose 20' Long

Specifications subject to change without prior notice. Version 10062025.



540 E. Old Highway 56 Olathe, KS 66061-4640 USA